

FLOTATION
RADIAL

F1 Traction

Implement Low Pressure Tyres



LEGAL NOTICE



EATD | European Agriculture Tyre Distributors B.V.

Industriestraat 12
3291 CC Strijen
The Netherlands

P.O. Box 5722
3290 AA Strijen
The Netherlands

CONTACT

info@tianli-tyre.com
www.tianli-tyre.com

status: 01/2017

All information without guarantee.
We assume no liability for printing
errors.



FLOTATION RADIAL

F1 Traction | Implement Low Pressure Tyres | Pattern F1 Traction



- high load capacity
- 65 km/h approval
- good self-cleaning properties
- suitable for grassland
- low ground compaction
- low rolling resistance
- suitable for on/off-the-road agricultural service on tractors, trailers and agricultural implements





FLOTATION RADIAL

F1 Traction | Implement Low Pressure Tyres | Pattern F1 Traction

	tyre size	TT/TL	load/speed index	measured rim width	unloaded		static loaded radius	rolling circumference	Inflation pressure	load capacity								tread depth
					outer diameter	section width				static	10 km/h	25 km/h	30 km/h	40 km/h	50 km/h	60 km/h	65 km/h	
					inch	mm				mm	kg	kg	kg	kg	kg	kg	kg	
R17	500/50R17 IMP	TL	132A8	16.00	925	497	412	2780	100	1950	1650	1400	1320	1180	-	-	-	15
									120	2180	1850	1570	1480	1320	-	-	-	
									160	2570	2180	1855	1750	1560	-	-	-	
									200	2940	2490	2120	1990	1780	-	-	-	
									240	3300	2800	2380	2240	2000	-	-	-	
	560/45R22.5	TL	152D	16	1072	538	480,5	3220	100	2935	2300	2015	1930	1735	1540	1365	1275	15
									120	3270	2560	2245	2150	1930	1720	1520	1420	
									160	3870	3030	2660	2540	2290	2035	1800	1680	
									200	4400	3445	3020	2890	2600	2315	2050	1910	
									240	4935	3860	3390	3240	2920	2600	2295	2145	
R22.5	500/60R22.5 IMP	TL	155D	16.00	1186	483	537	3558	100	3920	3070	2690	2575	2320	2060	1820	1705	26
									120	4370	3420	3000	2870	2580	2300	2030	1900	
									160	5170	4045	3550	3390	3060	2720	2405	2250	
									200	5880	4600	4040	3860	3480	3095	2740	2560	
									240	6595	5160	4530	4330	3900	3470	3070	2870	
	560/45R22.5 IMP	TL	152D	16.00	1085	523	486	3266	100	3590	2810	2470	2360	2120	1890	1670	1560	25
									120	4000	3130	2750	2630	2365	2105	1860	1740	
									160	4735	3705	3250	3110	2800	2490	2200	2060	
									200	5390	4220	3700	3540	3185	2835	2510	2340	
									240	6040	4730	4150	3970	3570	3180	2810	2630	
600/50R22.5 IMP	TL	159D	20.00	1185	580	536	3556	100	4430	3465	3040	2910	2620	2330	2060	1925	26	
								120	4930	3860	3390	3240	2915	2590	2290	2140		
								160	5840	4570	4010	3830	3450	3070	2715	2540		
								200	6640	5200	4560	4360	3930	3490	3090	2890		
								240	7445	5830	5115	4890	4400	3920	3460	3240		



FLOTATION RADIAL

F1 Traction | Implement Low Pressure Tyres | Pattern F1 Traction

	tyre size	TT/TL	load/speed index	measured rim width	unloaded		static loaded radius	rolling circumference	inflation pressure	load capacity								tread depth
					outer diameter	section width				static	10 km/h	25 km/h	30 km/h	40 km/h	50 km/h	60 km/h	65 km/h	
					inch	mm				mm	mm±2.5%	mm±2.5%	kpa	kg	kg	kg	kg	
R22.5	710/45R22.5 IMP	TL	165D	24.00	1189	678	530	3567	100	5210	4080	3580	3420	3080	2740	2425	2265	26
									120	5800	4540	3990	3810	3430	3050	2700	2520	
									160	6870	5380	4720	4510	4060	3610	3195	2990	
									200	7820	6120	5370	5130	4620	4110	3640	3400	
									240	8765	6860	6020	5755	5180	4610	4080	3810	
									280	9590	7510	6590	6300	5670	5050	4460	4170	
									320	10305	8065	7080	6765	6090	5420	4790	4480	
									360	11130	8710	7650	7310	6580	5860	5180	4840	
									400	11845	9270	8140	7780	7000	6230	5510	5150	
R26.5	600/55R26.5 IMP	TL	165D	20.00	1361	587	608	4046	100	5210	4080	3580	3420	3080	2740	2425	2265	26
									120	5800	4540	3990	3810	3430	3050	2700	2520	
									160	6870	5380	4720	4510	4060	3610	3195	2990	
									200	7820	6120	5370	5130	4620	4110	3640	3400	
									240	8765	6860	6020	5755	5180	4610	4080	3810	
									280	9590	7510	6590	6300	5670	5050	4460	4170	
									320	10305	8065	7080	6765	6090	5420	4790	4480	
									360	11130	8710	7650	7310	6580	5860	5180	4840	
									400	11845	9270	8140	7780	7000	6230	5510	5150	
R26.5	710/50R26.5 IMP	TL	170D	24.00	1342	678	596	4034	100	6070	4750	4170	3985	3590	3190	2825	2640	26
									120	6760	5290	4645	4440	4000	3560	3145	2940	
									160	8000	6260	5500	5255	4730	4210	3720	3480	
									200	9110	7130	6260	5980	5385	4790	4240	3960	
									240	10210	7990	7015	6700	6040	5370	4750	4440	
									280	11180	8750	7680	7340	6610	5880	5200	4860	
									320	12005	9395	8250	7880	7100	6315	5585	5220	
									360	12970	10150	8910	8515	7670	6820	6035	5640	
									400	13800	10800	9480	9060	8160	7260	6420	6000	