

IMPLEMENT RADIAL

R100

Implement Tyres



LEGAL NOTICE



EATD | European Agriculture Tyre Distributors B.V.

Industriestraat 12
3291 CC Strijen
The Netherlands

P.O. Box 5722
3290 AA Strijen
The Netherlands

CONTACT

info@tianli-tyre.com
www.tianli-tyre.com

status: 11/2017

All information without guarantee.
We assume no liability for printing
errors.



IMPLEMENT RADIAL

R100 | Implement Tyres | Pattern R100



- the tyre offers good traction on uneven ground
- excellent lateral stability due to reinforced casing construction
- low ground compaction through wide contact area
- special wear resistant tread compound for enhanced performance
- suitable for grassland operations





IMPLEMENT RADIAL

R100 | Implement Tyres | Pattern R100

	tyre size	TT/TL	load/speed index	measured rim width	unloaded		static loaded radius	rolling circumference	Inflation pressure	load capacity								tread depth
					outer diameter	section width				static	10 km/h	25 km/h	30 km/h	40 km/h	50 km/h	60 km/h	65 km/h	
					inch	mm				mm	mm±2.5%	mm±2.5%	kpa	kg	kg	kg	kg	
R15	31×15.50R15	TL	122B	13LB	792	391	355	2374	100	1860	1215	900	870	810	810			19
									120	2070	1350	1000	960	900	900			
									160	2480	1620	1200	1155	1080	1080			
									200	2830	1845	1365	1315	1230	1230			
									240	3140	2050	1515	1460	1365	1365			
									280	3450	2250	1665	1605	1500	1500			
R17	425/55R17	TL	134D	13.00	881	425	398	2635	100	2340	1830	1610	1540	1380	1230	1090	1020	27
									120	2580	2020	1775	1700	1530	1360	1200	1120	
									160	3070	2400	2110	2020	1815	1615	1430	1335	
									200	3510	2750	2410	2305	2075	1850	1630	1525	
									240	3900	3050	2680	2560	2310	2050	1815	1695	
									280	4240	3320	2910	2785	2510	2230	1970	1840	
									320	4580	3590	3150	3010	2710	2410	2130	1990	
									350	4875	3815	3350	3200	2880	2565	2270	2120	