

FLOTATION
RADIAL

Ride King



LEGAL NOTICE



EATD | European Agriculture Tyre Distributors B.V.

Industriestraat 12
3291 CC Strijen
The Netherlands

P.O. Box 5722
3290 AA Strijen
The Netherlands

CONTACT

info@tianli-tyre.com
www.tianli-tyre.com

status: 11/2017

All information without guarantee.
We assume no liability for printing
errors.



FLOTATION RADIAL

Ride King



- high load capacity
- 65 km/h approval
- excellent self-cleaning properties for safe driving on and off-the-road
- low ground compaction
- specially suitable for transport on paved roads
- low rolling resistance for fuel saving and comfortable ride
- extended wear compound for enhanced tyre lifetime





FLOTATION RADIAL

Ride King

	tyre size	TT/TL	load/speed index	measured rim width	unloaded		static loaded radius	rolling circumference	Inflation pressure	load capacity								tread depth
					outer diameter	section width				static	10 km/h	25 km/h	30 km/h	40 km/h	50 km/h	60 km/h	65 km/h	
					inch	mm				mm	mm±2.5%	mm±2.5%	kpa	kg	kg	kg	kg	
R30.5	NEW 750/60R30.5	TL	181D	24,00	1660	770	738	4992	100	8350	6530	5735	5480	4940	4390	3880	3630	25
									120	9300	7280	6390	6100	5500	4890	4325	4040	
									160	11005	8610	7560	7225	6510	5790	5120	4785	
									200	12520	9800	8600	8220	7405	6590	5825	5445	
									240	14040	10990	9645	9220	8300	7390	6530	6105	
									280	15370	12030	10560	10090	9090	8085	7150	6680	
									320	16510	12920	11340	10840	9760	8685	7680	7180	
									360	17840	13960	12250	11710	10550	9380	8300	7755	
									400	18975	14850	13035	12460	11220	9980	8830	8250	