



Type Size	Pattern	TRA Code	Tread Depth	Load Speed Index	Star	Rim	OD/mm	SW/mm	pressure	Load	Speed
15.5R25	TUL300	L-3	27	176/A2	★★	12,00	1276	397	600	7100	10
16.00R25 (445/95R25)	TUE100	E-1	25,4	177/B	★★	11,25	1475	454	700	7300	50
				174/F	★★	11,25	1475	454	900	6700	80
17.5R25	TUL300	L-3	27	182/A2	★★	14,00	1347	449	650	8500	10
	TUL580	L-5S	65	182/A2	★★	14,00	1398	442	650	8500	10
18.00R25	TUE300	E-3	32	185/B	★★	13,00	1623	504	700	9250	50
20.5R25	TUL300	L-3	31	193/A2	★★	17,00	1482	533	650	11500	10
23.5R25	TUL300	E-3	41	185/B	★★	19,50	1602	607	525	9250	50
		L-3		201/A2	★★	19,50	1602	607	650	14500	10
		IND-3		206/A2	★★★	19,50	1602	607	800	17000	10
	TUL400	E-4	55	185/B	★★	19,50	1660	600	525	9250	50
		L-4		201/A2	★★	19,50	1660	600	650	14500	10
		IND-3		206/A2	★★★	19,50	1660	600	800	17000	10
26.5R25	TUL500	L-5	97,5	209/A2	★★	22,00	1760	690	650	18500	10
	TUL580	L-5S	97,5	209/A2	★★	22,00	1760	690	650	18500	10
	TUL300	E-3	38	193/B	★★	22,00	1735	686	525	11500	50
		L-3		209/A2	★★	22,00	1735	686	650	18500	10
		IND-3		214/A2	★★★	22,00	1735	686	800	21200	10
	TUL400	E-4	55	193/B	★★	22,00	1788	685	525	11500	50
		L-4		209/A2	★★	22,00	1788	685	650	18500	10
	29.5R25	TUL300	E-3	42	200/B	★★	25,00	1860	769	525	14000
L-3			216/A2		★★	25,00	1860	769	650	22400	10
IND-3			221/A2		★★★	25,00	1860	769	800	25750	10
TUL400		E-4	57,5	200/B	★★	25.00/3.5	1906	760	525	14000	50
		L-4		216/A2	★★	25.00/3.5	1906	760	650	22400	10
35/65R33	TUL500	L-5	97	224/A2	★★	28,00	2029	889	650	28000	10
				229/A2	★★★	28,00	2029	889	800	32500	10
21.00R35	TUE400	E-4	55	201/B	★★	15.00/3.0	2032	590	700	14500	50
24.00R35	TUE400	E-4	63	209/B	★★	17.00	2160	653	700	18500	50
33.25R35	TUE390	E-3	43,4	212/B	★★	27.00	2222	861	525	20000	50
37.25R35	TUE390	E-3	47,4	218/B	★★	31,00	2389	946	525	23600	50
27.00R49	TUE400	E-4	64,8	223/B	★★	19,50	2689	738	700	27250	50
30.00R51	TUE400	E-4	77	230/B	★★	22,00	2887	825	700	33500	50
33.00R51	TUE400	E-4	94,9	235/B	★★	24,00	3047	911	700	38750	50
36.00R51	TUE400	E-4	83,3	241/B	★★	26,00	3190	979	700	46250	50
37.00R57	TUE400	E-4	92	245/B	★★	27,00	3424	1031	700	51500	50
40.00R57	TUE400	E-4	98,1	250/B	★★	29,00	3577	1116	700	60000	50
50/80R57	TUE410	E-4	98	257/B	★★	34,00	3556	1270	600	73000	50
56/80R63	TUE410	E-4	106	266/B	★★	41,00	3956	1422	600	95000	50
59/80R63	TUE410	E-4	118	268/B	★★	44,00	4069	1499	600	100000	50



TIANLI Databooks with all technical details about our complete program:  
[www.tianli-tyre.com/en/downloads](http://www.tianli-tyre.com/en/downloads)



Simply download all brochures and databooks as **TIANLI APP!**



[www.tianli-tyre.com](http://www.tianli-tyre.com)



European Agriculture Tyre Distributors B.V.

Industriestraat 12,  
NL-3291 CC Strijen,  
Netherlands

Phone: +31 (0) 78 629 1210  
E-Mail: [info@tianli-tyre.com](mailto:info@tianli-tyre.com)  
Ust-ID: NL 8543 88734 B01

IBAN: NL41 RABO 0192 0925 88  
SWIFT: RABONL2U

Bank: Rabobank  
Address: Reedijk 8  
City: Heinenoord